

SES Helavia

Flexibel Neoprene Plain Marker Sleeves

Technical



Material

Shore hardness A	40 ± 5
Tensile strength	> 8 MPa
Elongation at rupture	> 600%
Operating temperature	≥ +90 °C
Low temperature resistance	-30 °C
Packaging	1,000 pieces, from type A5 500 pieces, yellow/green 100 pieces
Mounting tools	Available
Flame resistance	UL 94-V0/M3

Neoprene: extremely elastic, mechanically strong, extremely good resistance to ozone, fair resistance to oils

Type	Cable diameter mm	Length mm	Wall thickness mm	Sleeve colour				
				Black	Red	Yellow	Green	Blue
A0	1.25-2.0	20	0.5	1334 0000	1334 0018	1334 0026	1334 0034	1334 0042
A1	1.75-3.5	20	0.5	1334 0263	1334 0271	1334 0280	1334 0298	1334 0301
A1 K	2.5-5.5	25	0.9	1334 2509	1334 2516	1334 2513	1334 2512	1334 2511
A1bis	2.5-4.5	20	0.6	1334 0506	1334 0514	1334 0522	1334 0530	1334 0549
A2	3.0-6.0	25	0.6	1334 0760	1334 0778	1334 0786	1334 0794	1334 0808
A2 K	4.0-8.0	30	1.2	1334 2762	1334 2769	1334 2766	1334 2765	1334 2764
A3	5.0-9.0	25	0.7	1334 1006	1334 1014	1334 1022	1334 1030	1334 1049
A4	7.5-12.0	30	0.8	1334 1260	1334 1278	1334 1286	1334 1294	1334 1308
A5	10.5-15.0	35	0.9	1334 1502	1334 1510	1334 1529	1334 1537	1334 1545
A8	12.0-20.0	50	1.2	1334 1766	1334 1774	1334 1782	1334 1790	1334 1804
A9	14.0-23.0	50	1.3	1334 2002	1334 2010	1334 2029	1334 2030	1334 2045
A10	17.0-28.0	50	1.3	1334 2266	1334 2274	1334 2282	1334 2290	1334 2304

Type	Cable diameter mm	Length mm	Wall thickness mm	Sleeve colour				
				Grey	White	Purple	Brown	Yellow / Green
A0	1.25-2.0	20	0.5	1334 0050	1334 0069	1334 0077	1334 0085	1336 3409
A1	1.75-3.5	20	0.5	1334 0310	1334 0328	1334 0336	1334 0344	1336 3450
A1 K	2.5-5.5	25	0.9	1334 2518	1334 2510	1334 2517	1334 2515	-
A1bis	2.5-4.5	20	0.6	1334 0557	1334 0565	1334 0573	1334 0581	1336 3470
A2	3.0-6.0	25	0.6	1334 0816	1334 0824	1334 0832	1334 0840	1336 3557
A2 K	4.0-8.0	30	1.2	1334 2771	1334 2763	1334 2770	1334 2768	-
A3	5.0-9.0	25	0.7	1334 1057	1334 1065	1334 1073	1334 1081	1336 3603
A4	7.5-12.0	30	0.8	1334 1316	1334 1324	1334 1332	1334 1340	1336 3654
A5	10.0-15.0	35	0.9	1334 1553	1334 1561	1334 1570	1334 1588	1336 3700
A8	12.0-20.0	50	1.2	1334 1812	1334 1813	1334 1768	1334 1847	1336 3751
A9	14.0-23.0	50	1.3	1334 2090	1334 2060	1334 2089	1334 2088	1336 3808
A10	17.0-28.0	50	1.3	1334 2352	1334 2350	1334 2351	1334 2347	1336 3859

AVT Industrial Components BV, GIVATEC BV and AGCO BV are part of AVT Wiring & Connecting

AVT Industrial Components BV
+31 (0)40 20 88 088
sales@avtic.com
www.avtic.com

GIVATEC BV
+32 (0)16 400 500
sales@givatec.com
www.givatec.com

AGCO BV
+31 (0)40 208 80 044
sales@agco.nl
www.agco.nl

SES Helavia

Flexibel Neoprene Plain Marker Sleeves

Type	Cable diameter mm	Length mm	Wall thickness mm	Sleeve colour				
				Orange	Pink	Light blue		
A0	1.25-2.0	20	0.5	1334 0107	1334 0090	1334 0091		
A1	1.75-3.5	20	0.5	1334 0350	1334 0290	1334 0291		
A1 K	2.5-5.5	25	0.9	1334 2514	1334 2519	1334 2520		
A1bis	2.5-4.5	20	0.6	1334 0603	1334 0590	1334 0591		
A2	3.0-6.0	25	0.6	1334 0867	1334 0795	1334 0796		
A2 K	4.0-8.0	30	1.2	1334 2767	1334 2772	1334 2773		
A3	5.0-9.0	25	0.7	1334 1103	1334 1090	1334 1091		
A4	7.5-12.0	30	0.8	1334 1283	1334 1341	1334 1342		
A5	10.5-15.0	35	0.9	1334 1515	1334 1590	1334 1591		
A8	12.0-20.0	50	1.2	1334 1806	1334 1848	1334 1849		
A9	14.0-23.0	50	1.3	1334 2047	1334 2091	1334 2092		
A10	17.0-28.0	50	1.3	1334 2306	1334 2353	1334 2354		

Type	Also available in length mm
A0	10, 15, 25 or 30 mm
A1	10, 15, 25, 30 and 40 mm
A1bis	10, 15, or 25 mm
A2	10, 15, 20, 30, 40 or 50 mm
A3	10, 20 or 40 mm
A4	40 or 50 mm
A5	40 or 50 mm
A8	40 mm
A1K	15, 30 or 40 mm