





7/8" Circular Connectors

Moulded cable connectors







Technical drawing									
Product description									
Connector type		Circular connector with moulded cable		Circular connector with moulded cable		Circular connector with moulded cable			
Conforms to		--		--		--			
Construction type		7/8"-16 UN		7/8"-16 UN		7/8"-16 UN			
Description		Circular connector 7/8" series with moulded cable		Circular connector 7/8" series with moulded cable		Circular connector 7/8" series with moulded cable			
Housing type		Straight 180° Angled 90°		Straight 180° Angled 90°		Straight 180° Angled 90°			
Cable gland		Moulded cable		Moulded cable		Moulded cable			
Contacts type		Female		Female		Female			
Number of contacts		3poles (2p.+P.E.)		4poles (3p.+P.E.)		5poles (4p.+P.E.)			
Housing colour		Black		Black		Black			
Technical data									
Type of termination		Contacts to solder wires		Contacts to solder wires		Contacts to solder wires			
Contacts material		Brass+Gold flash		Brass+Gold flash		Brass+Gold flash			
Coupling nut type		Knurl round		Knurl round		Knurl round			
7/8 " coupling nut material		Brass+Nickel plated		Brass+Nickel plated		Brass+Nickel plated			
7/8 " coupling nut torque		0.8 N*m		0.8 N*m		0.8 N*m			
Rated voltage		250V AC / DC		250V AC / DC		250V AC / DC			
Rated current		12A		9A		9A			
O-ring material		NBR		NBR		NBR			
Cable type		PVC/PVC CEI2022		PVC/PVC CEI2022		PVC/PVC CEI2022			
Cable jacket colour		Black		Black		Black			
No.Conductors / Section		3x1.50mm²		4x1.50mm²		5x1.50mm²			
Conductor colours		Yellow/green; Brown; Blue;		Black; Blue; Brown; Yellow/green;		White; Blue; Yellow/green; Brown; Black;			
Cable diameter		ø7.8mm (±0.3)		ø10.2mm (±0.3)		ø11mm (±0.3)			
Cable lenght		1m		1m		1m			
Packaging									
Qty/Bag		1 pc / bag		1 pc / bag		1 pc / bag			
Other accessories options									
-									
Notes: Connectors available with different features: See the general features and codification scheme page									

7/8" Circular Connectors

Moulded cable connectors



Technical drawing								
								
								
Product description								
Connector type	Circular connector with moulded cable			Circular connector with moulded cable		Circular connector with moulded cable		
Conforms to	--			--		--		
Construction type	7/8"-16 UN			7/8"-16 UN		7/8"-16 UN		
Description	Circular connector 7/8" series with moulded cable			Circular connector 7/8" series with moulded cable		Circular connector 7/8" series with moulded cable		
Housing type	Straight 180°		Angled 90°		Straight 180°		Angled 90°	
Cable gland	Moulded cable			Moulded cable		Moulded cable		
Contacts type	Male			Male		Male		
Number of contacts	3poles (2p. +P.E.)			4poles (3p. +P.E.)		5poles (4p. +P.E.)		
Housing colour	Black			Black		Black		
Technical data								
Type of termination	Contacts to solder wires			Contacts to solder wires		Contacts to solder wires		
Contacts material	Brass+Gold flash			Brass+Gold flash		Brass+Gold flash		
Coupling nut type	Knurl round			Knurl round		Knurl round		
7/8 " coupling nut material	Brass+Nickel plated			Brass+Nickel plated		Brass+Nickel plated		
7/8 " coupling nut torque	0.8 N*m			0.8 N*m		0.8 N*m		
Rated voltage	250V AC / DC			250V AC / DC		250V AC / DC		
Rated current	12A			9A		9A		
O-ring material	-			-		-		
Cable type	PVC/PVC CEI2022			PVC/PVC CEI2022		PVC/PVC CEI2022		
Cable jacket colour	Black			Black		Black		
No.Conductors / Section	3x1.50mm²			4x1.50mm²		5x1.50mm²		
Conductor colours	Yellow/green; Brown; Blue;			Black; Blue; Brown; Yellow/green;		White; Blue; Yellow/green; Brown; Black;		
Cable diameter	ø7.8mm (±0.3)			ø10.2mm (±0.3)		ø11mm (±0.3)		
Cable lenght	1m			1m		1m		
Packaging								
Qty/Bag	1 pc / bag			1 pc / bag		1 pc / bag		
Other accessories options								
-								
Notes: Connectors available with different feautres: See the general features and codification scheme page								