


Non-rusting and highly flexible material protection conduit; extremely robust; double folded metal profile



Properties

IP 40 to EN/IEC 60529

Good screening factor (EMC)

Highly flexible

Increased resistance to tear, pressure and impact

Conforms to RoHS guideline

Temperature range

600 °C

Delivery variants

Further diameters and lengths available on request

Design material

Profiled metal strip, stainless steel (INOX); twice rolled profile

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Abrasion-proof, oil resistant and polyurethane coated metal protection conduit; extremely robust and liquid tight: double folded metal profile

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

