

Cable trunking

GF-A12/8

Cable trunking SES with slots and base punching



GF-A12/8




GF-A12/8


Material:	rigid PVC quality 9051 LF
Colour:	grey RAL7030
Operating temperatures:	-5 to +65°C
Density:	1,56
Volume resistivity:	10 ¹⁵ Ω.cm
Dielectric strength:	15 kV/mm
Specifications:	V0 UL94 CSTB:M2
Standard length:	2 meters
Double sided adhesive:	upon request
Minimum delivery:	1 complete packing (with lids)
Applications:	used with cable of large diameter



type	trunking art. no.	 m	outside dim.		cables per trunking (filling 50 %)			lids (alone) art. no.	 m
			H mm	W mm	1 mm ²	1,5 mm ²	2,5 mm ²		
GF-A12/8 100 x 100	0845 0276 013	12	100	100	671	551	461	0845 0630 013	12
GF-A12/8 100 x 150	0845 0273 013	12	100	150	1043	856	716	0845 0636 013	12




C3/1-01



C3/1-01



C3/1-02



C3/1-02



C3/5-01




C3/6-01



C3/6-01



D4/6-01



Cable trunking

GF-A12/8

Cable trunking SES with slots and base punching



GF-A12/8



GF-A12/8

