





M12 Circular Connectors

Panel mount - A-coded







Technical drawing							
							
Product description							
Connector type		Circular connector panel mount		Circular connector panel mount		Circular connector panel mount	
Conforms to		IEC 61076-2-101		IEC 61076-2-101		IEC 61076-2-101	
Construction type		M12 A-Coded		M12 A -Coded		M12 A -Coded	
Description		Circular connector M12 series,panel mount		Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series to panel mount with PVC soldered wires.	
Housing type		Frontal panel side	Back panel side	Frontal panel side	Back panel side	Frontal panel side	Back panel side
Contacts type		Female		Female		Female	
Number of contacts		4poles		4poles		4poles	
Fixing thread		PG9		PG9 + CUT		PG9	
Cut size		-		13.3mm		-	
Technical data							
Type of termination		Contacts to solder wires		Contacts suitable for solder PCB		Contacts to solder wires	
Contacts material		Brass + Gold flash		Brass + Gold flash		Brass + Gold flash	
Housing material		Brass + Nickel plated		Brass + Nickel plated		Brass + Nickel plated	
Mobile nut material		Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)	
M12 coupling nut torque		0.4 N*m		0.4 N*m		0.4 N*m	
Rated voltage		250V AC / DC		250V AC / DC		250V AC / DC	
Rated current		4A		4A		4A	
O-ring material		NBR		NBR		NBR	
Cable type		-		-		PVC	
No.Conductors / Section		-		-		4 x 0.25mm²	
Conductor colours		-		-		Brown; White; Blue; Black	
Cable diameter		-		-		-	
Cable lenght		-		-		0.3m	
Packaging							
Qty/Bag		Not defined		Not defined		Not defined	
Other accessories options							
See accessories section							
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section							

M12 Circular Connectors

Panel mount - A-coded







Technical drawing							
STD.							
							
Product description							
Connector type	Circular connector panel mount			Circular connector panel mount		Circular connector panel mount	
Conforms to	IEC 61076-2-101			IEC 61076-2-101		IEC 61076-2-101	
Construction type	M12 A-Coded			M12 A-Coded		M12 A-Coded	
Description	Circular connector M12 series,panel mount			Circular connector M12 series,panel mount, with contacts suitable for solder PCB.		Circular connector M12 series,panel mount, with PVC soldered wires.	
Housing type	Frontal panel side	Back panel side	Frontal panel side	Back panel side	Frontal panel side	Back panel side	
Contacts type	Female		Female		Female		
Number of contacts	5poles		5poles		5poles		
Fixing thread	PG9		PG9 + CUT		PG9		
Cut size	-		13.3mm		-		
Technical data							
Type of termination	Contacts to solder wires			Contacts suitable for solder PCB		Contacts to solder wires	
Contacts material	Brass + Gold flash			Brass + Gold flash		Brass + Gold flash	
Coupling nut type	Brass + Nickel plated			Brass + Nickel plated		Brass + Nickel plated	
Housing material	Brass + Nickel plated (SW17)			Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)	
Mobile nut material	0.4 N*m			0.4 N*m		0.4 N*m	
Rated voltage	60V AC / DC			60V AC / DC		60V AC / DC	
Rated current	4A			4A		4A	
O-ring material	NBR			NBR		NBR	
Cable type	-			-		PVC	
No.Conductors / Section	-			-		5 x 0.25mm ²	
Conductor colours	-			-		Brown; White; Blue; Black;Grey	
Cable diameter	-			-		-	
Cable lenght	-			-		0.3m	
Packaging							
Qty/Bag	Not defined			Not defined		Not defined	
Other accessories options							
See accessories section							
Notes: Connectors available with different feautres; See the general features and codification scheme page See the cables list section							

M12 Circular Connectors

Panel mount - A-coded







Technical drawing							
							
Product description							
Connector type		Circular connector panel mount		Circular connector panel mount		Circular connector panel mount	
Conforms to		IEC 61076-2-101		IEC 61076-2-101		IEC 61076-2-101	
Construction type		M12 A-Coded		M12 A-Coded		M12 A-Coded	
Description		Circular connector M12 series,panel mount		Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series,panel mount with PVC soldered wires.	
Housing type		Frontal panel side	Back panel side	Frontal panel side	Back panel side	Frontal panel side	Back panel side
Contacts type		Female		Female		Female	
Number of contacts		12poles		12poles		12poles	
Fixing thread		PG9		PG9 + CUT		PG9	
Cut size		-		13.3mm		-	
Technical data							
Type of termination		Contacts to solder wires		Contacts suitable for solder PCB		Contacts to solder wires	
Contacts material		Brass + Gold flash		Brass + Gold flash		Brass + Gold flash	
Housing material		Brass + Nickel plated		Brass + Nickel plated		Brass + Nickel plated	
Mobile nut material		Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)	
M12 coupling nut torque		0.4 N*m		0.4 N*m		0.4 N*m	
Rated voltage		30V AC / DC		30V AC / DC		30V AC / DC	
Rated current		1,5A		1,5A		1,5A	
O-ring material		NBR		NBR		NBR	
Cable type		-		-		PVC	
No.Conductors / Section		-		-		12 x 0.14mm²	
Conductor colours		-		-		Bn;Bu;Wh;Gn;Pk;Ye;Bk;Gy;Rd;Vt;Pk;Gy;Rd;Bu	
Cable diameter		-		-		-	
Cable lenght		-		-		0.3m	
Packaging							
Qty/Bag		Not defined		Not defined		Not defined	
Other accessories options							
See accessories section							
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section							

M12 Circular Connectors

Panel mount - A-coded








Technical drawing							
STD.							
							
Product description							
Connector type	Circular connector panel mount			Circular connector panel mount		Circular connector panel mount	
Conforms to	IEC 61076-2-101			IEC 61076-2-101		IEC 61076-2-101	
Construction type	M12 A-Coded			M12 A-Coded		M12 A-Coded	
Description	Circular connector M12 series,panel mount			Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series,panel mount with PVC soldered wires.	
Housing type	Frontal panel side	Back panel side	Frontal panel side	Back panel side	Frontal panel side	Back panel side	
Contacts type	Male		Male		Male		
Number of contacts	4poles		4poles		4poles		
Fixing thread	PG9		PG9 + CUT		PG9		
Cut size	-		13.3mm		-		
Technical data							
Type of termination	Contacts to solder wires			Contacts suitable for solder PCB		Contacts to solder wires	
Contacts material	Brass + Gold flash			Brass + Gold flash		Brass + Gold flash	
Housing material	Brass + Nickel plated			Brass + Nickel plated		Brass + Nickel plated	
Mobile nut material	Brass + Nickel plated (SW17)			Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)	
M12 coupling nut torque	0.4 N*m			0.4 N*m		0.4 N*m	
Rated voltage	250V AC / DC			250V AC / DC		250V AC / DC	
Rated current	4A			4A		4A	
O-ring material	NBR			NBR		NBR	
Cable type	-			-		PVC	
No. Conductors / Section	-			-		4 x 0.25mm²	
Conductor colours	-			-		Brown; White; Blue; Black	
Cable diameter	-			-		-	
Cable lenght	-			-		0.3m	
Packaging							
Qty/Bag	Not defined			Not defined		Not defined	
Other accessories options							
See accessories section							
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section							

M12 Circular Connectors

Panel mount - A-coded







Technical drawing									
STD.									
									
WITH CUT									
									
Product description									
Connector type	Circular connector panel mount			Circular connector panel mount		Circular connector panel mount			
Conforms to	IEC 61076-2-101			IEC 61076-2-101		IEC 61076-2-101			
Construction type	M12 A-Coded			M12 A-Coded		M12 A-Coded			
Description	Circular connector M12 series,panel mount			Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series,panel mount with PVC soldered wires.			
Housing type	Frontal panel side		Back panel side		Frontal panel side		Back panel side		
Contacts type	Male			Male		Male			
Number of contacts	5poles			5poles		5poles			
Fixing thread	PG9			PG9 + CUT		PG9			
Cut size	-			13.3mm		-			
Technical data									
Type of termination	Contacts to solder wires			Contacts suitable for solder PCB		Contacts to solder wires			
Housing material	Brass + Gold flash			Brass + Gold flash		Brass + Gold flash			
Mobile nut material	Brass + Nickel plated			Brass + Nickel plated		Brass + Nickel plated			
M12 coupling nut material	Brass + Nickel plated (SW17)			Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)			
M12 coupling nut torque	0.4 N*m			0.4 N*m		0.4 N*m			
Rated voltage	60V AC / DC			60V AC / DC		60V AC / DC			
Rated current	4A			4A		4A			
O-ring material	NBR			NBR		NBR			
Cable type	-			-		PVC			
No.Conductors / Section	-			-		5 x 0.25mm²			
Conductor colours	-			-		Brown; White; Blue; Black;Grey			
Cable diameter	-			-		-			
Cable lenght	-			-		0.3m			
Packaging									
Qty/Bag	Not defined			Not defined		Not defined			
Other accessories options									
See accessories section									
Notes: Connectors available with different feautres: See the general features and codification scheme page See the cables list section									

M12 Circular Connectors

Panel mount - A-coded







Technical drawing STD. 													
Product description													
Connector type		Circular connector panel mount			Circular connector panel mount		Circular connector panel mount		Circular connector panel mount		Circular connector panel mount		
Conforms to		IEC 61076-2-101			IEC 61076-2-101		IEC 61076-2-101		IEC 61076-2-101		IEC 61076-2-101		
Construction type		M12 A-Coded			M12 A-Coded		M12 A-Coded		M12 A -Coded		M12 A -Coded		
Description		Circular connector M12 series,panel mount			Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series,panel mount with PVC soldered wires.		Circular connector M12 series,panel mount with PVC soldered wires.		
Housing type		Frontal panel side		Back panel side		Frontal panel side		Back panel side		Frontal panel side		Back panel side	
Contacts type		Male			Male			Male			Male		
Number of contacts		8poles			8poles			8poles			8poles		
Fixing thread		PG9			PG9 + CUT			PG9 + CUT			PG9		
Cut size		-			13.3mm			13.3mm			-		
Technical data													
Type of termination		Contacts to solder wires			Contacts suitable for solder PCB			Contacts suitable for solder PCB			Contacts to solder wires		
Contacts material		Brass+Gold flash			Brass+Gold flash			Brass+Gold flash			Brass+Gold flash		
Housing material		Brass+Nickel plated			Brass+Nickel plated			Brass+Nickel plated			Brass+Nickel plated		
Mobile nut material		Brass+Nickel plated (SW17)			Brass+Nickel plated (SW17)			Brass+Nickel plated (SW17)			Brass+Nickel plated (SW17)		
M12 coupling nut torque		0.4 N*m			0.4 N*m			0.4 N*m			0.4 N*m		
Rated voltage		30V AC/DC			30V AC/DC			30V AC/DC			30V AC/DC		
Rated current		2A			2A			2A			2A		
O-ring material		NBR			NBR			NBR			NBR		
Cable type		-			-			-			PVC		
No.Conductors / Section		-			-			-			8 x 0.25mm²		
Conductor colours		-			-			-			White;Brown;Green;Yellow;Grey;Pink;Blue;Red		
Cable diameter		-			-			-			-		
Cable lenght		-			-			-			0.3m		
Packaging													
Qty/Bag		Not defined			Not defined			Not defined			Not defined		
Other accessories options													
See accessories section													
Notes:													
Connectors available with different feautres:													
See the general features and codification scheme page													
See the cables list section													

M12 Circular Connectors

Panel mount - A-coded








Technical drawing												
STD. 												
Product description												
Connector type		Circular connector panel mount		Circular connector panel mount		Circular connector panel mount						
Conforms to		IEC 61076-2-101		IEC 61076-2-101		IEC 61076-2-101						
Construction type		M12 A-Coded		M12 A-Coded		M12 A-Coded						
Description		Circular connector M12 series,panel mount		Circular connector M12 series to panel mount with contacts suitable for solder PCB.		Circular connector M12 series,panel mount with PVC soldered wires.						
Housing type		Frontal panel side	Back panel side	Frontal panel side	Back panel side	Frontal panel side	Back panel side					
Contacts type		Male		Male		Male						
Number of contacts		12poles		12poles		12poles						
Fixing thread		PG9		PG9 + CUT		PG9						
Cut size		-		13.3mm		-						
Technical data												
Type of termination		Contacts to solder wires		Contacts suitable for solder PCB		Contacts to solder wires						
Contacts material		Brass + Gold flash		Brass + Gold flash		Brass + Gold flash						
Housing material		Brass + Nickel plated		Brass + Nickel plated		Brass + Nickel plated						
Mobile nut material		Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)		Brass + Nickel plated (SW17)						
M12 coupling nut torque		0.4 N*m		0.4 N*m		0.4 N*m						
Rated voltage		30V AC / DC		30V AC / DC		30V AC / DC						
Rated current		1,5A		1,5A		1,5A						
O-ring material		NBR		NBR		NBR						
Cable type		-		-		PVC						
No.Conductors / Section		-		-		12 x 0.14mm²						
Conductor colours		-		-		Bn;Bu;Wh;Gn;Pk;Ye;Bk;Gy;Rd;Vt;Pk;Gy;Rd;Bu						
Cable diameter		-		-		-						
Cable lenght		-		-		0.3m						
Packaging												
Qty/Bag		Not defined		Not defined		Not defined						
Other accessories options												
See accessories section												
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section												

M12 Circular Connectors

Panel mount - A-coded



Technical drawing



Product description

Connector type	Circular connector panel mount	Circular connector panel mount	Circular connector panel mount	Circular connector panel mount
Conforms to	IEC 61076-2-101	IEC 61076-2-101	IEC 61076-2-101	IEC 61076-2-101
Construction type	M12 A-Coded	M12 A-Coded	M12 A-Coded	M12 A-Coded
Description	Circular connector M12 series,panel mount with FLANGE	Circular connector M12 series,panel mount with FLANGE	Circular connector M12 series,panel mount with FLANGE	Circular connector M12 series,panel mount with FLANGE

Housing type	Frontal panel side	Frontal panel side	Frontal panel side	Frontal panel side
Contacts type	Female	Female	Female	Female
Number of contacts	4poles	5poles	8poles	12poles
Fixing thread	-	-	-	-
Cut size	-	-	-	-

Technical data

Common data				
Type of termination	Contacts to solder wires	Contacts to solder wires	Contacts to solder wires	Contacts to solder wires
Contacts material	Brass+Gold flash	Brass+Gold flash	Brass+Gold flash	Brass+Gold flash
Housing material	Brass+Nickel plated	Brass+Nickel plated	Brass+Nickel plated	Brass+Nickel plated
Mobile nut material	-	-	-	-
M12 coupling nut torque	0.4 N*m	0.4 N*m	0.4 N*m	0.4 N*m
Rated voltage	250V AC/DC	60V AC/DC	30V AC/DC	30V AC/DC
Rated current	4A	4A	2A	1.5A
O-ring material	-	-	-	-
Cable type	-	-	-	-
No. Conductors / Section	-	-	-	-
Conductor colours	-	-	-	-
Cable diameter	-	-	-	-
Cable lenght	-	-	-	-

Packaging

Qty/Bag	Not defined	Not defined	Not defined	Not defined
---------	-------------	-------------	-------------	-------------

Other accessories options

See accessories section


Notes:

Connectors available with different features:
See the general features and codification scheme page
See the cables list section

M12 Circular Connectors

Panel mount - A-coded





Technical drawing 				
Product description				
Connector type	Circular connector panel mount	Circular connector panel mount	Circular connector panel mount	Circular connector panel mount
Conforms to	IEC 61076-2-101	IEC 61076-2-101	IEC 61076-2-101	IEC 61076-2-101
Construction type	M12 A-Coded	M12 A-Coded	M12 A-Coded	M12 A-Coded
Description	Circular connector M12 series, panel mount with FLANGE	Circular connector M12 series, panel mount with FLANGE	Circular connector M12 series, panel mount with FLANGE	Circular connector M12 series, panel mount with FLANGE
Housing type	Frontal panel side	Frontal panel side	Frontal panel side	Frontal panel side
Contacts type	Male	Male	Male	Male
Number of contacts	4poles	5poles	8poles	12poles
Fixing thread	-	-	-	-
Cut size	-	-	-	-
Technical data				
Type of termination	Contacts to solder wires	Contacts to solder wires	Contacts to solder wires	Contacts to solder wires
Contacts material	Brass+Gold flash	Brass+Gold flash	Brass+Gold flash	Brass+Gold flash
Housing material	Brass+Nickel plated	Brass+Nickel plated	Brass+Nickel plated	Brass+Nickel plated
Mobile nut material	-	-	-	-
M12 coupling nut torque	0.4 N*m	0.4 N*m	0.4 N*m	0.4 N*m
Rated voltage	250V AC/DC	60V AC/DC	30V AC/DC	30V AC/DC
Rated current	4A	4A	2A	1.5A
O-ring material	-	-	-	-
Cable type	-	-	-	-
No.Conductors / Section	-	-	-	-
Conductor colours	-	-	-	-
Cable diameter	-	-	-	-
Cable length	-	-	-	-
Packaging				
Qty/Bag	Not defined	Not defined	Not defined	Not defined
Other accessories options				
See accessories section				
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section				

M12 Circular Connectors

Panel mount - A-coded





Technical drawing 			
			
Product description			
Connector type	Circular connector panel mount	Circular connector panel mount	Circular connector panel mount
Conforms to	IEC 61076-2-101	IEC 61076-2-101	IEC 61076-2-101
Construction type	M12 A-Coded	M12 A-Coded	M12 A-Coded
Description	Circular connector M12 series, panel mount, with screw contacts	Circular connector M12 series, panel mount, with screw contacts	Circular connector M12 series, panel mount, with screw contacts
Housing type	Back panel side	Back panel side	Back panel side
Contacts type	Female	Female	Female
Number of contacts	4poles	5poles	8poles
Fixing thread	PG9	PG9	PG9
Cut size	13.3mm	13.3mm	13.3mm
Technical data			
Type of termination	Screw contacts	Screw contacts	Screw contacts
Contact screw torque	0.2 N*m	0.2 N*m	0.2 N*m
Contacts material	Brass+Gold flash	Brass+Gold flash	Brass+Gold flash
Housing material	Brass+Nickel plated	Brass+Nickel plated	Brass+Nickel plated
Mobile nut material	Brass+Nickel plated (SW17)	Brass+Nickel plated (SW17)	Brass+Nickel plated (SW17)
M12 coupling nut torque	0.4 N*m	0.4 N*m	0.4 N*m
Rated voltage	250V AC / DC	60V AC / DC	30V AC / DC
Rated current	4A	4A	2A
O-ring material	NBR	NBR	NBR
Conductors cross section	From 0.14(26AWG) to 0.50mm ² (20AWG)	From 0.14(26AWG) to 0.50mm ² (20AWG)	From 0.14(26AWG) to 0.50mm ² (20AWG)
Packaging			
Qty/Bag	Not defined	Not defined	Not defined
Other accessories options			
See accessories section			
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section			

M12 Circular Connectors

Panel mount - A-coded



Technical drawing 			
			
Product description			
Connector type	Circular connector panel mount	Circular connector panel mount	Circular connector panel mount
Conforms to	IEC 61076-2-101	IEC 61076-2-101	IEC 61076-2-101
Construction type	M12 A-Coded	M12 A-Coded	M12 A-Coded
Description	Circular connector M12 series, panel mount, with screw contacts	Circular connector M12 series, panel mount, with screw contacts	Circular connector M12 series, panel mount, with screw contacts
Housing type	Back panel side	Back panel side	Back panel side
Contacts type	Male	Male	Male
Number of contacts	4poles	5poles	8poles
Fixing thread	PG9	PG9	PG9
Cut size	13.3mm	13.3mm	13.3mm
Technical data			
Type of termination	Screw contacts	Screw contacts	Screw contacts
Contact screw torque	0.2 N*m	0.2 N*m	0.2 N*m
Contacts material	Brass + Gold flash	Brass + Gold flash	Brass + Gold flash
Housing material	Brass + Nickel plated	Brass + Nickel plated	Brass + Nickel plated
Mobile nut material	Brass + Nickel plated (SW17)	Brass + Nickel plated (SW17)	Brass + Nickel plated (SW17)
M12 coupling nut torque	0.4 N*m	0.4 N*m	0.4 N*m
Rated voltage	250V AC / DC	60V AC / DC	30V AC / DC
Rated current	4A	4A	2A
O-ring material	NBR	NBR	NBR
Conductors cross section	From 0.14(26AWG) to 0.50mm ² (20AWG)	From 0.14(26AWG) to 0.50mm ² (20AWG)	From 0.14(26AWG) to 0.50mm ² (20AWG)
Packaging			
Qty/Bag	Not defined	Not defined	Not defined
Other accessories options			
See accessories section			
Notes: Connectors available with different features: See the general features and codification scheme page See the cables list section			